

## RENDIMENTI AL 100% E AL 30% DEL CARICO NOMINALE

CALDAIA	MODELLO	POTENZA NOMINALE (kW)	RENDIMENTO RICHIESTO (30% Pn)	RENDIMENTO MISURATO (30% Pn)	RENDIMENTO RICHIESTO (100% Pn)	RENDIMENTO MISURATO (100% Pn)	% CO2 FUMI	TEMPERATURA FUMI * (°C)
NOUVELLE ELITE 50	520 - 520 EL	23.3	84.1	86.5	86.73	90	6.2	130
NOUVELLE ELITE 100	112/120-112EL/120EL	23.3	84.1	85.5	86.73	90.1	6.2	130
NOUVELLE ELITE 100	127 - 127 EL	31.4	84.49	86.3	86.99	90	6.2	130
NOUVELLE ELITE 400	420R - 420R EL	23.3	84.1	87.2	86.73	90.1	6.2	130
NOUVELLE ELITE T.F.	T.F. 120 - T.F. 120 EL	23.3	84.1	85.4	86.73	90	-	-
NOUVELLE ELITE FLUSS 50	50 - 50 EL	23.3	84.1	87.1	86.73	90.1	-	-
NOUVELLE ELITE FLUSS	FLUSS - FLUSS EL	23.3	84.1	87.8	86.73	91	-	-
NOUVELLE ELITE FLUSS	FLUSS 24 EL	27.9	84.34	87.5	86.89	90.5	-	-
XIGNAL	XIGNAL	27.9	84.34	87.8	86.89	90.8	-	-
INNOX	21	24.4	84.16	87.2	86.76	90.3	-	-
INNOX	25	29	84.38	87.4	86.92	90.5	-	-
NOXIA	27/45 - 27/100	31.4	84.49	87.5	86.99	91	-	-
RENDIMAX	15 - 15 EL	17	83.69	88	86.46	90.5	6.8	135
RENDIMAX	21 - 21 EL	24	84.14	88.1	86.76	90.2	6.8	135
RENDIMAX	27 - 27 EL	31	84.47	88	86.98	90.4	6.8	135
RENDIMAX	33 - 33 EL	38	84.74	87.9	87.16	90.3	6.8	135
RENDIMAX PV	15 - 15 EL	17	83.69	88	86.46	90.5	6.8	135
RENDIMAX PV	21 - 21 EL	24	84.14	88.1	86.76	90.2	6.8	135
RENDIMAX PV	21 - 21 EL	31	84.47	88	86.98	90.4	6.8	135
COMPETITION	22 - 22 EL	25.6	84.22	87.5	86.82	90.1	6.5	135
COMPETITION	27 - 27 EL	31	84.47	86.6	86.98	90.2	6.5	135
TANTAQUA	15/3 - 15/3 EL	17	83.69	88	86.46	90.5	6.8	135
TANTAQUA	21/4 - 21/4 EL	24	84.14	88.1	86.76	90.2	6.8	135
TANTAQUA	27/5 - 27/5 EL	31	84.47	88	86.98	90.4	6.8	135
DUOTERM RENDIMAX	15	17	83.69	88	86.46	90.5	6.8	135
DUOTERM RENDIMAX	21	24	84.14	88.1	86.76	90.2	6.8	135
DUOTERM RENDIMAX	27	31	84.47	88	86.98	90.4	6.8	135
LN RENDIMAX	41 - 41 EL	47.3	85.02	88.2	87.35	90.3	7	135
LN RENDIMAX	54 - 54 EL	62.9	84.4	88.3	87.6	90.4	7	135
LN RENDIMAX	68 - 68 EL	78.7	85.69	87.9	87.79	90.1	7	135
LN RENDIMAX	81 - 81 EL	94.3	85.92	88.5	87.95	90.6	7	135
LN RENDIMAX	99 - 99 EL	105	86.06	88.3	88.04	90.4	6	130
LN RENDIMAX	117 - 117 EL	136	86.4	88.6	88.27	90.7	6	130
LN RENDIMAX	132 - 132 EL	153	86.55	88.4	88.37	90.5	6	130
LN RENDIMAX	146 - 146 EL	170	86.69	88.2	88.46	90.2	6	130
BLUE POINT	B.P. 80/11	238.5	87.13	90	88.75	91.4	6.5	130
BLUE POINT	B.P. 88/12	262.8	87.26	90.1	88.84	91.5	5.0	100
BLUE POINT	B.P. 96/13	286.8	87.37	90.1	88.92	91.5	5.6	110
BLUE POINT	B.P. 104/14	310.8	87.48	90.2	88.98	91.6	6.2	120
ZENTRAL	ZL 2/12 - ZQ 2/12	175.2	86.73	90	88.49	91.4	-	-
ZENTRAL	ZL 2/13 - ZQ 2/13	191.2	86.84	90.1	88.56	91.5	-	-
ZENTRAL	ZL 2/14 - ZQ 2/14	207.2	86.95	90.1	88.63	91.5	-	-
ZENTRAL	ZL 3/11	238.5	87.13	90	88.75	91.4	-	-
ZENTRAL	ZL 3/12	262.8	87.26	90.1	88.84	91.5	-	-
ZENTRAL	ZL 3/13	286.8	87.37	90.1	88.92	91.5	-	-
ZENTRAL	ZL 3/14	310.8	87.48	90.2	88.98	91.6	-	-
ZENTRAL	ZL 4/12 - ZQ 4/12	350.4	87.63	90.1	89.09	91.5	-	-
ZENTRAL	ZL 4/13 - ZQ 4/13	382.4	87.75	90.1	89.17	91.5	-	-
ZENTRAL	ZL 4/14 - ZQ 4/14	414.4	87.81	90.2	89.2	91.6	-	-

\* La temperatura fumi è al netto della temperatura ambiente.