

Dati tecnici <Batis Plus>

Altezza H (mm)	Codice articolo	Largh. L (mm)	Interas. N (mm)	Peso P (kg)	Conten. d'acqua L (litri)	Esp. n	Resa term. EN 442 [W] $\Delta t=50K$ 75/65/20°C	Resistenza Potenza [W]
719	53000070050 **	490	455	6,26	2,29	1,22	372	400
	53000070055 **	540	505	6,44	2,37	1,21	410	400
	53000070060 **	590	555	7,04	2,59	1,21	439	400
	53000070075 **	740	705	8,12	2,88	1,19	535	400
	53000070100 **	990	955	10,00	3,47	1,17	698	800
1109	53000110050 **	490	455	9,17	3,54	1,24	542	400
	53000110055 **	540	505	9,47	3,60	1,22	597	400
	53000110060 **	590	555	10,35	3,93	1,22	637	800
	53000110075 **	740	705	12,03	4,42	1,19	779	800
	53000110100 **	990	955	14,80	5,31	1,15	1014	1200
1460	53000140050 **	490	455	11,89	4,59	1,25	685	800
	53000140055 **	540	505	12,22	4,64	1,24	755	800
	53000140060 **	590	555	13,35	5,07	1,24	804	800
	53000140075 **	740	705	15,52	5,76	1,21	983	800
	53000140100 **	990	955	19,19	6,84	1,18	1278	1200
1850	53000180050 **	490	455	14,80	5,84	1,26	843	800
	53000180055 **	540	505	15,25	5,87	1,25	929	800
	53000180060 **	590	555	16,66	6,42	1,25	991	800
	53000180075 **	740	705	19,32	7,19	1,23	1210	1200
	53000180100 **	990	955	23,98	8,68	1,21	1575	1200